

### Shutter Alarm

Model : PDAS-02



### Features

- It consists of an alarm body to be installed on the shutter and a robust metal sensor to be installed in the floor.
- The metal sensor which is to be fit in the floor is specially designed for rough use as expected while closing shutters. It can also withstand heavy weights expected while moving stock and has slanting design on both sides, providing ease of stock movement using trolleys.
- This alarm system can be installed on a shutter and it gives out a loud siren on intrusion.
- Highly reliable key-enabled alarm system for single shutter.
- Piezo electric buzzer of 120 dB results in a loud siren.
- On entering if the alarm is not disabled within 15 seconds, it gives out a loud siren, indicating intrusion.
- Once the siren starts ringing, it can only be turned off with the key.
- Alarm body is made up of metal and is robust, sturdy and secure.
- Operates on AA cells, 4 nos. (Supplied with the machine). Requires no electric connection.
- IP-65 certified product.
- Long battery life of about 8 months.
- Easy installation with only 4 nut-bolts fitting for alarm and 2 screws fitting for the sensor.

**Applications :** Shops, storage godowns, homes, offices, banks, ATMs, cold storage rooms.

**Dimensions :** • Alarm body : 200(L) x 78(W) x 46(H) mm • Metal sensor for shutter : 80(L) x 42(W) x 8(H) mm